

T-Lok Barrier



This precast concrete F-type barrier has an Austroads Safety Barrier Assessment Panel (ASBAP) approval of 100km/h MASH TL-3.

The barrier offers the lowest deflection result of any approved freestanding barrier system.

Anti-gawk / debris screens can be fitted to the barriers providing additional protection for workers and motorists.

Our fleet is new and in excellent condition. We offer a turn-key barrier rental solution and all deployments will be solely managed and certified by the Road Safety Rental team.

Approved by



SPECIFICATIONS

Effective Length	3.65m
Height	810mm
Width	610mm
Weight	2600kg
Weight Per Metre	722kg
Successfully Tested To	MASH TL-3
ASBAP Approval To	100km/h TL-3
MASH TL-3 Deflection	1.27m (100km/h, 2270kg)
Amount Transportable Per Semi Truck	9
Multiple End Treatments Can Be Used	Yes (QuadGuard CZ / SLED)
Sight/Debris Screen Options Bolt On	Yes
Lightweight	No
High Containment	No
Safe Redirection	Yes
Fast Deployment/Retrieval	Yes
No Anchoring Required	Yes
Economical To Transport	No
Maintenance Free	Yes
Durable	No

- ✓ Freestanding barrier
- ✓ Low deflection
- ✓ Safe redirection
- ✓ Fast deployment and retrieval
- ✓ No anchoring required
- ✓ Maintenance free
- ✓ Multiple end treatments can be used
- ✓ Sight / debris screen options bolt on
- ✓ Dedicated 3.6m fleet so we can accommodate radii as low as 30m
- ✓ Engineered wedge piece to allow for tighter radii

